



## GX-FL26W-KN-22K-BK 2200K

Modèle Model	Voltage Volts	Fréquence Frequency	Wattage Power
GX-FL26W-KN-22K-BK	120-277VAC	50/60HZ	26W

  

CRI	CCT	Lumens	Angle de faisceau Beam Angle	Durée Life
≥70	2200K	3380LM	100°	100 000 heures 100000 Hrs



- Projecteur extérieur DEL haute performance
- Conception unique de coque pour un refroidissement optimal et l'économie d'énergie
- Support articulé pour une installation facile
- Lumens : 3380LM
- Angle de faisceau : 100°
- Tension nominale : 120/277 VCA
- Température de couleur : 2200K
- CRI : >70CRI
- Fréquence : 50 - 60Hz
- Durée de vie jusqu'à 100 000 heures
- Certificats ETL, DLC
- Garantie de 5 ans

- High performance LED exterior floodlight
- Unique hull design for a optimal cooling and energy saving
- Articulated bracket for easy installation
- Lumens: 3380LM
- Beam Angle: 100°
- Nominal voltage: 120/277 VAC
- Color temperature: 2200K
- CRI: >70CRI
- Frequency: 50 - 60Hz
- Lifetime up to 100,000 hours
- ETL certificates, DLCs
- 5 year warranty

## Applications

Projecteur DEL extérieur  
Outlook LED Flood Light

